

## OptiCare



Personally optimized therapeutic mattress

# Smart technology

#### **OPTIMIZED CARE**

The mattress is personally optimized for each patient based on his or her weight, height and position on the mattress.

### SUPERIOR IMMERSION AND ENVELOPMENT


Excessive pressure on the risk points is eliminated by even distribution across the entire body area thanks to superior immersion and envelopment.

- IMMERSION: spreads the pressure over a larger area, especially bony prominences.
- body parts etc. and not increasing pressure in these areas.

Optimization Detection System: 6 detectors to sense the patient's immersion level to automatically optimize the mattress pressure to suit each patient's weight and position.




#### TYPICAL ACTIVE MATTRESS




#### FULLY AUTOMATIC PRESSURE SETTING

OptiCare automatically adjusts the pressure settings to provide the optimal conditions for each patient with minimal staff intervention.

- ENVELOPMENT: allows the mattress to conform to irregularities such as linen folds,





## Easy and effective care



LINET | OptiCare

### AUTOMATIC FOOT EXTENSION

The heel section of the mattress can be automatically adjusted when the bed frame is extended.



#### INTELLIGENT HEEL ZONE

The heel section has a 7 degree slope now and is lined with a softer foam giving the patient superior comfort.



## Even more effective



#### SLEEP MODE

This mode reduces speed and noise to minimise disturbance of the patient during sleep. The clinical effect of the mattress is maintained even when switching to the sleep mode.

#### MATTRESS COVER

The top part of the cover consists of highly moisture- and vapour-permeable (MVP) two-way stretch material.


A full 360-degree zip to allow easy removal for cleaning or replacement

 The zipper is covered by a flap to protect the mattress against fluid ingress

The new OptiCare therapeutic mattress is fully compatible with ICU beds – Multicare and Eleganza 5.



### OptiCare at a glance



#### TECHNICAL SPECIFICATIONS

Safe working load	550 lb
Length	84 in
Width	34 in
Height	8 in
Weight	25.5 lb

	Max Inflate	after 30 minutes, returns back to OPT
	Microclimate management modes	high, low, off
	CPR	1 button CPR, automatic inflation after 60 minutes
o	Transport mode	Yes

